



Search



MSDS 250,000+

MSDS : GENERAL PURPOSE PLASTIC CEMENT #10-324
 CAS : 141-78-6
 67-64-1
 123-86-4
 71-36-3
 108-88-3
 64-17-5
 NAME : ethyl acetate (sara iii)
 acetone (sara iii)
 n-butyl acetate (sara iii)
 n-butyl alcohol (sara iii)
 toluene (sara iii)
 ethyl alcohol (ethanol)
 nitrocellulose

Catalog of Chemical Suppliers, Buyers, Custom Synthesis Companies And Equipment Manufacturers
 [GENERAL PURPOSE PLASTIC CEMENT #10-324 141-78-6 67-64-1 123-86-4 71-36-3 108-88-3 64-17-5]

Suppliers:

Not Available

Buyers:

Not Available

===== Product Identification =====

MSDS NAME:GENERAL PURPOSE PLASTIC CEMENT #10-324
 NIIN:00-063-1387
 MSDS Number: BHGDD
 === Responsible Party ===
 Company:GC ELECTRONICS CO,SUB OF HOUSEHOLD INTERNATIONAL C
 Address:1801 MORGAN ST
 Box:1209
 City:ROCKFORD
 State:IL
 ZIP:61105-1209
 Country:US
 Info Phone Num:815-968-9661
 Emergency Phone Num:815-968-9661
 Preparer's Name:V.HAGMAN
 CAGE:E0032
 === Contractor Identification ===
 Company:GC ELECTRONICS CO,SUB OF HOUSEHOLD INTERNATIONAL C
 Address:1801 MORGAN ST
 Box:1209
 City:ROCKFORD
 State:IL
 ZIP:61105-1209
 Country:US
 Phone:815-968-9661
 CAGE:E0032

Company:GC THORSEN
Address:1801 MORGAN STREET
Box:City:ROCKFORD
State:IL
ZIP:61105
Country:US
Phone:815-968-9661
CAGE:72653

=====
Composition/Information on Ingredients
=====

Name:ETHYL ACETATE (SARA III)
CAS:141-78-6
RTECS #:AH5425000
Fraction by Wt: 35.0%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 20.0%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: <5.0%
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:E01400000
Fraction by Wt: <5.0%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 5.0%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Name:NITROCELLULOSE
Fraction by Wt: <15.0%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF
EYES,SKIN,RESPIRATORY OR G.I.TRACTS;CNS EFFECTS LIKE
HEADACHE,DIZZINESS,NAUSEA,VOMITING AND POSSIBLE
UNCONSCIOUSNESS;REDNESS OR BURNS OF EYES/SKIN
POSSIBLE.CHRONIC:BLOOD OR KIDNEY DISORDERS.

Explanation of Carcinogenicity:DATA PER MGF
Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:24.0F,-4.4C
Lower Limits:1.2
Upper Limits:21.1
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL
IGNITON SOURCES;CONTAIN FREE LIQUID IF POSSIBLE;USE SUITABLE INERT
ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL IN AN APPROVED
CONTAINER.
Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT
CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID
PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES.
USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED
IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.
Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.
Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER
Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK
CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.
Supplemental Safety and Health
AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:=55.6C, 132.F
Spec Gravity:0.954
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR LIQUID,SOLVENT ODOR
Percent Volatiles by Volume:86.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS,ACIDS AND BASES
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OTHER UNIDENTIFIED COMPONENTS(TOXIC)

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE MADE
IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.

*** END OF RECORD ***

[Search More](#)



ALL PAGES On Chemical Property IN THIS GROUP

NAME

[B-6-665 RED EPOXY INSUL LAB NO. 34536](#)

[LATEX HOUSE & TRIM PAINT #300](#)

[GENERAL PURPOSE PLASTIC CEMENT #10-324](#)

[RACON 500](#)

[RACON 500](#)

CAS

75-09-2
1330-20-7
78-93-3
64742-95-6
74-98-6
75-28-5
62-38-4
57-55-6
25265-77-4
124-68-5
141-78-6
67-64-1
123-86-4
71-36-3
108-88-3
64-17-5
75-71-8
75-37-6
75-45-6
76-15-3

RACON 500	75-71-8 75-37-6
RACON 502	75-45-6 76-15-3
RACON 502	75-45-6 76-15-3
AVIATION GASOLINES	8006-61-9 71-43-2 78-00-2
165 0084,VERSAMAT DEVLPR STATER, TYPE B	64-19-7 7647-15-6 7732-18-5
RACON 114	76-14-2
JET FUEL JP5	64742-47-8 109-86-4
RACON 12	75-71-8
INSTANT ACTIVATOR 141-001	1310-58-3 7757-83-7 584-08-7 7601-54-9
RACON 113	76-13-1
276Z DEVELOPER STARTER	
HYDROCHLORIC ACID;CODE:P1125	7647-01-0 7732-18-5 7440-38-2 56-23-5 67-66-3 7439-92-1
RACON 114	76-14-2
RACON 114	76-14-2
N-450-13 THINNER	108-88-3 64742-48-9 64742-89-8
RACON 114	76-14-2
RACON 12	75-71-8
RACON 22	75-45-6
NOVAWELD C	109-99-9 108-94-1
BEN-GAY ORIGINAL OINTMENT(F322/0730)	119-36-8 89-78-1 8006-54-0 7732-18-5 8002-74-2 8002-74-2
EXTINGUISHER,FIRE,VAPORIZING LIQUID	353-59-3 7727-37-9
EXTINGUISHER,FIRE,VAPORIZING LIQUID	353-59-3 7727-37-9
EA 9313 EPOXY RESIN, PART B	
EA 9313 EPOXY, PART A	
EXTINGUISHER,FIRE,HALOGENATED AGENT	353-59-3 7727-37-9
COATING, POLYURETHANE SAND 33303 ID754208	108-65-6 108-88-3 78-93-3 14464-46-1 14464-46-1 14808-60-7 13463-67-7
COATING, POLYURETHANE SAND 33303 ID754201	123-86-4 822-06-0

RACON 500	75-71-8 75-37-6
XAW-6487 PART B,CATALYST-REDUCER	108-10-1 71-36-3 123-86-4 110-80-5 1330-20-7 107-98-2
XAW-6487 PART B,CATALYST-REDUCER	108-10-1 71-36-3 123-86-4 110-80-5 1330-20-7 107-98-2
EA 9602.3 .080 PSF EPOXY RESIN TAPE BEN-GAY LOTION/74300-00470/	119-36-8 89-78-1 8006-54-0 7732-18-5 8012-95-1 9004-99-3 1323-39-3 99-76-3 94-13-3
BLACK TONER FOR DC-211/213RE/313Z COPIER	1333-86-4 31714-55-3 1344-28-1 25213-39-2
BLACK DEVELOPER FOR DC-211	1309-37-1 1314-13-2 1309-48-4 1317-39-1
E-58A EMULSIFIER (SEE SUPP DATA) TURCO POROKLEEN	107-21-1 1310-73-2 497-19-8 6834-92-0 25155-30-0 26027-38-3
MISTY PAINT STRIPPER 375	75-09-2 8052-41-3 67-56-1 74-98-6
MISTY PAINLESS STAINLESS	75-28-5 8042-47-5
ABLEBOND 190-3	7440-22-4 7440-50-8
INSTAPAK PORT CLEANER BLO	96-48-0 124-38-9
HOT STICK WIPING CLOTH CHANCE GLOSS RESTORER PART A	2807-30-9 68477-31-7 1330-20-7
CHANCE GLOSS RESTORER PART B	1330-20-7 2807-30-9
STATICIDE READY TO USE EDP/WP	67-63-0 8001-54-5 68424-95-3 64-17-5
PARTS CLEANER	5989-27-5